

TLL151-5N-0500-01 Fuel Level Sensor, Cut-to-length



Document ref.: DDS_TLL151-5N-0500-01

06-Apr-21 Rev. 2

The T/LL151 liquid level sensor is designed for use in diesel fuel tanks and provides a variable voltage output suitable for connecting into PLCs and controllers.

This capacitance type level sensor is supplied in standard lengths and is designed to be cut-to-length and calibrated by the customer making it ideal for custom and urgent projects.

Part Description Prod. Group Technology Liquid Output Type Connector Thread Length

Performance

Output Accuracy

Materials

Enclosure Electrode Sensor Spacers End Plug Seals

Ratings

Sealing Pressure Shock Vibration Temperature

Electricals

Supply Voltage Supply Current Signal Protection

Alarm Output

Harness Information

Connector Output Alarm Output +ve supply location Ground TLL151-5N-0500-01 500MM, 0-5V, DIESEL, 1/2"NPT Fuel Level Sensor, Cut-to-length Capacitance Diesel Voltage Metri-pack 150 - 4 Pins 1/2" NPT 500 mm

0 - 5 V +/- 2%


30% Glass Filled Nylon Aluminum Alloy 6063 316 Stainless Steel Polypropylene PVC or G/F Nylon Viton and NBR


IP67 if fitted with mating connector 1 Bar (max) 50g, 6.3 ms 7.6 Grms -20 to +85 C

9-34 VDC 30 mA Over Voltage 80 VDC for 120s Reverse Polarity 12.5%, Ground on Fall

M/P 150-4P Pin C Pin B Pin D Pin A









Rochester Gauges, LLC 11616 Harry Hines Blvd., P.O. Box 29242, Dallas, TX 75229, USA +1(972) 241-2161 rochestergauges.com info@rochestergauges.com

E. & O. E. Rochester Gauges LLC and Fozmula Limited expects that you will conduct the testing and evaluation necessary to determine that these products are suitable for your application. Materials and specifications are subject to change without notice. JP 10-Jan-21 5.10 Rev. 1